

ELECTRICALLY OPERATED GREASE WORKING MACHINE ASTM D 217 - IP 50 - ISO 2137

The electrically operated grease working machine consists of a geared motor for 60 strokes/min mounted on a cast aluminium base with clamps to fix the grease workers. The number of strokes, continuously showed on a display, can be preset to stop the worker after any required number of strokes up to 100,000.



Dual-unit grease working machine

- Cast aluminium base, machine worked and enamel finished. Benchtop version.
- Geared motor unit for 60 strokes/min.
- One (single unit) or two crank flanges, cast iron.
- Programmable counter with six digits.
- One (single unit) or two grease workers.
- One (single unit) or two worker plates, 51 holes.
- Wrench for opening and closing of grease workers.
- For 220V - 50/60Hz connections: 600 W.
- English written user manual.
- Dimensions (l x w x h): mm 450 x 450 x 350 approx.
- Weight: kg 30 approx.
- CE marked.
- Single and dual units available.

AD0217-120 Single-unit grease working machine
AD0217-130 Dual-unit grease working machine

ACCESSORIES

AD0217-A00 Worker plate, 51 holes
AD0217-A01 Worker plate, 270 holes (FTMS 313.3)
AD0217-A02 Lip seal for rod
AD0217-A03 Overflow ring
AD0217-A04 Blank cup cover (used when preheating the sample prior to test)



Single-unit grease working machine

Specifications may vary without notice.

The apparatus includes the items listed aside the picture, accessories etc. should be purchased separately.

SCAVINI

Dott. Gianni Scavini & C.
Via Donne della Resistenza, 26 - 28831 Baveno (VB) Italy
Tel. +39-0323-924134 Fax +39-0323-924935
www.scavini.com