## APPARATUS FOR THE DETERMINATION OF OXIDATION CHARACTERISTICS OF DISTILLATE FUEL OIL ASTM D2274 - IP 388 - ISO 4263, 12205

The apparatus consists of a benchtop steel case containing an aluminium thermostatic block with a series of jackets for the introduction of the oxidation cells and a water dispenser for the condenser refrigeration: versions with variable area flowmeters or with mass flow controllers and touch-screen interface available.



AD2274-304

- Enamel finished benchtop steel case.
- Aluminium block bath with wells for test tubes, 48 mm diameter and 365 mm deep.
- Stainless steel electric heaters.
- Microprocessor thermoregulator with built-in temperature display, 0.1°C accuracy on versions -1xx or 8.4" Panel PC running Microsoft Windows Embedded with colour touchscreen interface on versions -3xx.
- Probe: PT100 RTD. Regulation accuracy ± 0.1°C. Working range: from ambient to 150 °C.
- Safety device against overheating.
- Easy access control box containing all the electronics and electrical parts. Aluminium control panel with english written indications.
- Oxygen inlet manifold with variable area flowmeters (-1xx) or high precision mass flow controllers (-3xx), 0-4 l/h.
- Water inlet manifold with valve connections for the mushroom condensers.
- Water outlet manifold.
- n° 1 thermometer jacket.
- English written user manual. CE marked.
- For connection to 220V 50/60Hz. Power consumption 1800 W (4 and 8-position units), 2500 W (12-position unit).
- Four, eight and twelve-place units available. Six-place unit on request.

AD2274-104	Four-place unit with variable area flowmeters. Dimensions (I x w x h): 700 x 600 x 1000 mm. Weight: 90 kg
AD2274-108	Eight-place unit with variable area flowmeters. Dimensions (I x w x h): 850 x 700 x 1000 mm. Weight: 130 kg
AD2274-112	Twelve-place unit with variable area flowmeters. Dimensions (I x w x h): 110 x 700 x 1000 mm. Weight: 160 kg
AD2274-304	Four-place unit with mass-flow controllers. Dimensions (I x w x h): 640 x 430 x 1000 mm. Weight: 90 kg
AD2274-308	Eight-place unit with mass-flow controllers. Dimensions (I x w x h): 640 x 490 x 1000 mm. Weight: 130 kg
AD2274-312	Twelve-place unit with mass-flow controllers. Dimensions (I x w x h): 760 x 430 x 1000 mm. Weight: 160 kg

## **ACCESSORIES**

AD2274-A00 Apparatus for filterable insolubles

AD2274-A01 Pack of 100 filters
AD2274-A02 Vacuum flask 500 ml
PT100 simulator

CAL003 Official Certificate for Pt100 simulator

## **CONSUMABLES**

AD2274-C00 Test tube

AD2274-C01 Mushroom condenser AD2274-C02 Oxygen delivery tube

TA040C-N00 ASTM 40C thermometer (+72°C/+126°C)

Specifications may vary without notice.

The apparatus includes the items listed aside the picture, accessories etc. should be purchased separately.

